

STANDARD HANDLES



2401



2402



3401



3701



All handles are available with other inlet connections and different colours for the handle grip.

Please advise your requirements.



Version according to DIN 8543 / DIN EN 731

Order no.	All handles with - inlet 3/8" LH external thread - outlet - M14x1 RH external thread			Working pressure	Maximum flow
	Shut-off valve	Valve for presetting of pilot flame	Quick opening trigger valve		
1010 2401	Hand wheel	no	yes	up to 4 bar	up to 14 kg/h
1010 2402	Hand wheel	no	no	up to 4 bar	up to 14 kg/h
1010 3401	Hand wheel	with slotted srew	yes	up to 4 bar	up to 14 kg/h
1010 3701	Hand wheel	with smal hand wheel	yes	up to 4 bar	up to 14 kg/h

EUROLINE HANDLES



4701



4702



4703



4704



All handles are available with other inlet connections and different models and colours for the handle grip.

Please advice your requirements.



Version according to DIN 8543 / DIN EN 731

Order no.	All handles with - inlet 3/8" LH external thread - outlet - M14x1 RH external thread			Working pressure	Maximum flow
	Shut-off valve	Valve for presetting of pilot flame	Quick opening trigger valve		
1010 4701	Hand wheel	no	yes	up to 4 bar	up to 14 kg/h
1010 4702	Hand wheel	no	no	up to 4 bar	up to 14 kg/h
1010 4703	Hand wheel	with smal hand wheel	yes	up to 4 bar	up to 14 kg/h
1010 4704	Hand wheel	with slotted screw	yes	up to 4 bar	up to 14 kg/h