

PLUMPER PROGRAM

Handle and torch attachments




Plumber handle



All handles are equipped with an integrated orifice needle for fine adjustments of the torch attachments


Order no.	Connections		Shut-off valve	Valve body	Diffuser	Handle grip	
	Inlet	Outlet				Painted in	Material
1010 5601 38	3/8" LH a.	M15x1 RH i.	Hand wheel	rotatable	infinitely variable	black	Wood

Turbo burners - Hard soldering



Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 5416	M 15 x 1	16	1,5 - 2,5	0,10	1,29	Brass
1030 5419	M 15 x 1	19	1,5 - 2,5	0,14	1,80	Brass
1030 5422	M 15 x 1	22	1,5 - 2,5	0,22	2,83	Brass

Turbo burners - Soft soldering



Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 5516	M 15 x 1	16	1,5 - 2,5	0,10	1,29	Brass
1030 5519	M 15 x 1	19	1,5 - 2,5	0,14	1,80	Brass
1030 5522	M 15 x 1	22	1,5 - 2,5	0,22	2,83	Brass


PLUMPER PROGRAM

Torch attachments

Paint burner




Point burner




Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 5614	M 15 x 1	16	1,5 - 2,5	0,10	1,29	Brass
1030 5615	M 15 x 1	19	1,5 - 2,5	0,14	1,80	Brass
1030 5516	M 15 x 1	22	1,5 - 2,5	0,22	2,83	Brass

Paint burner



Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 5624	M14x1 i.	70	0,5 - 1,5	0,10	1,29	Brass Steel nicklized

Turbo burner straight line



Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 5415	M 15 x 1	16	1,5 - 2,5	0,10	1,29	Brass

PLUMPER PROGRAM
Soldering iron complete
Accessories



Soldering iron complete



Consisting of:	Order no.	
Burner	1030 4219	
Kolbenhalter	1030 5412	
Flame arrester	1030 4220	
Copperbits	1030 4210	350 gr.
(350 and 500 gr.)	1030 4215	500 gr.

Order no.	Internal thread Inlet	Copperbits weight	Working pressure bar	Consumption 1,5 bar - Capacity	
				kg/h	kw/h
1030 5200	M15x1 a.	350gr.	1,5 - 2,5	0,10	1,29
1030 5250	M15x1 a.	500gr.	1,5 - 2,5	0,10	1,29

Holder for soldering iron



The holder can only be used in conjunction with the plumber handle

Order no.	Plumber handle with shaft 17 mm borehole 17 mm	Copperbit-shaft mm	Wing screw and holder inclusive	Material
1030 5412		6 to 8		Brass

Flame arrester



Can also be used in the plumber program

Order no.	Design steel nicklized	Borehole 8 mm for copperbits-shaft with wing srew and holder inclusive
1030 4220		

Copperbit 350 gr.



Can also be used in the standard program

Order no.	Design	Material	Copperbit-shaft	Weight gr.
1030 4210	as hammer form	copper	8 mm	350

Copperbit 500 gr.



Can also be used in the standard program

Order no.	Design	Material	Copperbit-shaft	Weight gr.
1030 4215	as hammer form	copper	8 mm	500

Copperbit 250 gr.



Can also be used in the standard program

Order no.	Design	Material	Copperbit-shaft	Weight gr.
1030 4212	as straight form	copper	8 mm	250