


TURBO BURNER POINTBURNER




Turbo burners - Hard soldering




Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 8112	M14x1 i.	12	1,5 - 2,5	0,04	0,51	Brass
1030 8116	M14x1 i.	16	1,5 - 2,5	0,10	1,29	Brass
1030 8119	M14x1 i.	19	1,5 - 2,5	0,14	1,80	Brass
1030 8122	M14x1 i.	22	1,5 - 2,5	0,22	2,83	Brass

Turbo burners - Soft soldering



Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 8216	M14x1 i.	16	1,5 - 2,5	0,10	1,29	Brass
1030 8219	M14x1 i.	19	1,5 - 2,5	0,14	1,80	Brass
1030 8222	M14x1 i.	22	1,5 - 2,5	0,22	2,83	Brass

Pointburners



Order no.	Internal thread Inlet	Diameter mm	Working pressure bar	Consumption 1,5 bar - Capacity		Material
				kg/h	kw/h	
1030 8316	M14x1 i.	16	1,5 - 2,5	0,03	0,39	Brass
1030 8319	M14x1 i.	19	1,5 - 2,5	0,10	1,29	Brass
1030 8322	M14x1 i.	22	1,5 - 2,5	0,20	2,57	Brass